

# **Ultraclean M2 Technical Data Sheet**



## Description

Ultraclean M2 is an alkaline detergent for general use in ultrasonic baths:

- Aqueous based product
- General purpose cleaning
- Improves surface tension & enhances ultrasonic performance
- Contains de-foaming agent

## **Applications**

Used in a wide range of applications including instrument decontamination in healthcare and cleaning different components in manufacturing and processing industries. Ultraclean M2 can be used to remove contaminants from plastics, glass, metals and other materials. (Not suitable for processing aluminium or other soft metals. Instead, please use Ultraclean SA)

### **Directions for Use**

Add 20-50ml of Ultraclean M2 per 1 Litre of water in the ultrasonic cleaner. Do not mix with other solutions. The required dosage will depend on your cleaning application and the level of contamination. Items should be rinsed with water and dried immediately after processing.

## **Technical Data**

These figures are typical and should not be interpreted as specifications, refer to the product safety data sheet for details

Characteristic	Value/Description
Appearance	Light brown liquid
Odour	Mild
рН (@ 1%)	11 - 12
Relative Density at 20°C	1.05

Supplied as:

- 6 x 1Litre Bottles (SKU: F50013)
- 25 Litre Drum (SKU: F50012)

## Disposal

When diluted to concentration of 5% or less, Ultraclean M2 is not hazardous to aquatic organisms and may be safely disposed of down the drain. Refer to regional or national regulations.

#### Storage

Store in a cool, dry place protected from frost and away from acids and strong oxidising agents. Store upright in original containers. Shelf-life up to 1year from date of manufacture.

Specifications are subject to change for continual improvements

Document No: C6008001-08 January 2023

