

Ultraclean CTA Technical Data Sheet



Description

Ultraclean CTA is an acidic detergent for metal descaling and rebrightingening in ultrasonic baths:

- To be diluted with water
- General purpose cleaning
- Metal descaling and rebrightingening
- Fair compatibility with aluminium

Applications

Used in a wide range of applications for cleaning, descaling and rebrightingening of different components in manufacturing, processing, servicing and within the food & beverage industries. Ultraclean CTA can be used on aluminium and other soft metals.

Directions for Use

Add 20-50g of Ultraclean CTA per 1 Litre of water in the ultrasonic cleaner. Do not mix with other solutions. The required dosage will depend on your cleaning application and the level of contamination. Items should be rinsed with water and dried immediately after processing.

Technical Data

These figures are typical and should not be interpreted as specifications, refer to the product safety data sheet for details

Characteristic	Value/Description
Appearance	White crystalline powder
Odour	Odourless
pH (@ 5%)	1.8
Relative Density at 20°C	1.665

Supplied as:

- 5kg Tub (SKU: F500035)
- 20kg Tub (SKU: F500034)

Disposal

When diluted to concentration of 5% or less, Ultraclean CTA is not hazardous to aquatic organisms and may be safely disposed of down the drain. Refer to regional or national regulations.

Storage

Store in a tightly-closed, original container in a dry and cool place. Store between 10°C and 30°C and protect from sunlight. Keep away from food and drink. Keep away from heat, sparks and open flame. Avoid contact with strong oxidising agents. Shelf-life up to 3years from date of manufacture.

Specifications are subject to change for continual improvements