

U2500H

25Litre Ultrasonic Bath (Heated)

Ultrawave's U-Series is compact and user friendly, offering effective cleaning and processing of small items in both professional and domestic applications.

These include healthcare, podiatry, tattooists, jewellers and many more.

Available in heated and unheated versions, the **U-Series** allows simple control of time (0 to 15 minutes) and temperature (ambient to 70°C) where heated options are selected.





The **U2500H** is a 25Litre ultrasonic bath with heating function to reduce processing time. Each **U-Series** is supplied complete with a stainless steel basket and ABS plastic lid, useable as a drip tray to collect excess water when the basket is removed from the tank.

The **U2500H** provides the cost benefits of excellent entry level ultrasonics with Ultrawave's long renowned quality and reliability.

Specifications are subject to change for continual improvements

Company Reg VAT No EROI No UW-DC-112-25 2558071 GB 827 1111 60 GB827111160001 Version 2



U2500H

25Litre Ultrasonic Bath (Heated)

Construction Case	304 Stainless Steel
Construction Tank	304 Stainless Steel
Control	Analogue (Time & Temperature)
Overall Dimensions	550 x 345 x 365mm (WxDxH)
Tank Dimensions	500 x 300 x 200mm (WxDxH)
Internal Basket Dimensions	470 x 265 x 130mm (WxDxH)
Maximum Capacity	28Litres
Working Capacity	25Litres
Ultrasonic Power	400W
Ultrasonic Power (per litre)	16W/Litre
Operating Frequency	32 – 38kHz
Maximum Heating Capacity	Ambient - 70°C
Maximum meaning capacity	Ambient - 70 C
Heater Power	650W
Heater Power	650W
Heater Power Timer	650W 0 - 15 minutes
Heater Power Timer Mains Connection	650W 0 - 15 minutes 220 - 240Vac (50 - 60Hz)
Heater Power Timer Mains Connection Drain Outlet	650W 0 - 15 minutes 220 - 240Vac (50 - 60Hz) ¹ /2" BSP valve (located at rear of machine)
Heater Power Timer Mains Connection Drain Outlet Lid Basket Gross Weight	650W 0 – 15 minutes 220 – 240Vac (50 – 60Hz) ¹ /2" BSP valve (located at rear of machine) ABS Plastic
Heater Power Timer Mains Connection Drain Outlet Lid Basket Gross Weight (inc. lid, basket & packaging)	650W 0 - 15 minutes 220 - 240Vac (50 - 60Hz) ¹ /2" BSP valve (located at rear of machine) ABS Plastic 304 Stainless Steel 18.5kg
Heater Power Timer Mains Connection Drain Outlet Lid Basket Gross Weight	650W 0 - 15 minutes 220 - 240Vac (50 - 60Hz) ¹ /2" BSP valve (located at rear of machine) ABS Plastic 304 Stainless Steel

(within 30days of purchase)

Company Reg VAT No EROI No UW-DC-112-25 2558071 GB 827 1111 60 GB827111160001 Version 2